

PC CONFIGURATOR CABLE

(USB - modular jack, isolated)

Functions & Features

- Used to connect the Signal Conditioners to the PC's USB port when setting parameters or monitoring operations of these devices on the PC Configurator Software

MODEL: COP-UM

ORDERING INFORMATION

- Code number: COP-UM

PACKAGE INCLUDES...

- Driver software CD-ROM (1)

GENERAL SPECIFICATIONS

Connection

USB: Type A connector

Modular Jack: 6-pin

Housing material: Resin (black)

Isolation: USB to modular jack

COMMUNICATION

Communication protocol: Full Speed USB2.0

(also usable with USB1.1 port)

Transmission speed: 38400 bps max.

CONNECTED DEVICE

USB: PC/AT compatible

OS (Windows 10 (32-bit, 64-bit), Windows 8.1 (32-bit, 64-bit), Windows 7 (32-bit, 64-bit), Windows Vista (32-bit))

Miniature jack side: Our Signal Conditioners

INSTALLATION

Operating temperature: -5 to +60°C (23 to 140°F)

Operating humidity: 30 to 90 %RH (non-condensing)

Weight: 75 g (2.6 oz)


PERFORMANCE

Insulation resistance: $\geq 100 \text{ M}\Omega$ with 500 V DC

Dielectric strength: 500 V AC @ 1 minute

(USB to Modular Jack)

DIMENSIONS unit: mm (inch)



Specifications are subject to change without notice.