


STRAIN GAUGE LOAD CELL

(Tension and compression type)

Functions & Features

- Rated capacity 100 N
- High accuracy



Hysteresis: ± 0.03 % R.O.

Repeatability: ± 0.03 % R.O.

Temperature effect on zero: ± 0.003 % R.O./ $^{\circ}\text{C}$

Temperature effect on output: ± 0.003 % LOAD/ $^{\circ}\text{C}$

Insulation resistance: 1000 M Ω or more (B/E 50V DC)

MODEL: LCCT-100-3

ORDERING INFORMATION

- Code number: LCCT-100-3

GENERAL SPECIFICATIONS

Cable type: 5 dia., 4-core shielded cable, split wire at the end

Cable length: 3 m

Body material: Aluminium

Rated flexure: 0.3 mm or less

Natural frequency: Approx. 0.42 kHz

INPUT SPECIFICATIONS

Rated capacity (R.C.): 100 N (10.2 kgf)

Safe overload: 150 % R.C.

Recommended excitation voltage: 10 V

Maximum excitation voltage: 15 V

Input terminal resistance: 410 $\Omega \pm 10 \Omega$

OUTPUT SPECIFICATIONS

Rated output (R.O.): 2 mV/V ± 5 %

Output terminal resistance: 350 $\Omega \pm 5 \Omega$

INSTALLATION

Compensated temperature range: -10 to +60 $^{\circ}\text{C}$ (14 to 140 $^{\circ}\text{F}$)

Safe temperature range: -10 to +70 $^{\circ}\text{C}$ (14 to 158 $^{\circ}\text{F}$)

Weight: 150 g (0.33 lb)


PERFORMANCE in percentage of span

Rated output error: ± 5 %

Zero balance: ± 10 % R.O.

Non-linearity: ± 0.03 % R.O.

EXTERNAL DIMENSIONS unit: mm [inch]



• WIRING COLOR

ITEM	COLOR
Excitation voltage +	Red
Excitation voltage -	White
Output signal +	Green
Output signal -	Blue
Shield	Yellow



Specifications are subject to change without notice.