


STRAIN GAUGE LOAD CELL

(Tension and compression type)

Functions & Features

- Rated capacity 10 N
- Very small type
- Easy to install with female screws on both ends



Hysteresis: ± 0.2 % R.O.

Repeatability: ± 0.1 % R.O.

Temperature effect on zero: ± 0.05 % R.O./°C

Temperature effect on output: ± 0.05 % LOAD/°C

Insulation resistance: 1000 MΩ or more (B/E 50V DC)

MODEL: LCCT-10-2

ORDERING INFORMATION

- Code number: LCCT-10-2

GENERAL SPECIFICATIONS

Cable type: 1.6 dia., 4-core shielded cable, split wire at the end

Cable length: 1 m

Body material: Aluminium

Rated flexure: 0.01 mm or less

Natural frequency: Approx. 4.6 kHz

INPUT SPECIFICATIONS

Rated capacity (R.C.): 10 N (1.02 kgf)

Safe overload: 150 % R.C.

Recommended excitation voltage: 2.5 V

Maximum excitation voltage: 5 V

Input terminal resistance: Approx. 350 Ω

OUTPUT SPECIFICATIONS

Rated output (R.O.): 0.7 mV/V ± 20 %

Output terminal resistance: Approx. 350 Ω

INSTALLATION

Compensated temperature range: -10 to +60 °C (14 to 140 °F)

Safe temperature range: -20 to +70 °C (-4 to 158 °F)

Weight: 3 g (0.11 oz)


PERFORMANCE in percentage of span

Rated output error: ± 20 %

Zero balance: ± 10 % R.O.

Non-linearity: ± 0.2 % R.O.

EXTERNAL DIMENSIONS unit: mm [inch]



• WIRING COLOR

ITEM	COLOR
Excitation voltage +	Red
Excitation voltage -	White
Output signal +	Green
Output signal -	Blue
Shield	Shield



Specifications are subject to change without notice.