

Plug-in Signal Conditioners MX-UNIT

RTD TRANSMITTER


(front configurable)

Functions & Features

- Converts an RTD input into a linearized process signal
- Field-programmable RTD type, temperature and output range
- Easy programming via front UP-DOWN keys with a help of 4-digit and 2-digit displays
- I/O signal inversion feature
- Isolation up to 2000 V AC
- Loop test output
- High-density mounting

Typical Applications

- Isolation between control room and field instrumentation
- Ideal for quick spare part



MODEL: MXR-[1]-[2][3]

ORDERING INFORMATION

- Code number: MXR-[1]-[2][3]

Specify a code from below for each of [1] through [3].
(e.g. MXR-V1-M2/Q)

- Specify the specification for option code /Q
(e.g. /C01/S01/SET)

[1] OUTPUT

Current

Z1: Range 0 - 20 mA DC (Load resistance 600Ω max.)

Voltage

V1: Range -1 - +1 V DC (Load resistance 1000Ω min.)

V2: Range -10 - +10 V DC (Load resistance 10kΩ min.)

[2] POWER INPUT

AC Power

M2: 100 - 240 V AC (Operational voltage range 85 - 264 V,

47 - 66 Hz)

DC Power

R: 24 V DC

(Operational voltage range 24 V ±10 %, ripple 10 %p-p max.)

P: 110 V DC

(Operational voltage range 85 - 150 V, ripple 10 %p-p max.)

[3] OPTIONS

blank: none

/Q: With options (specify the specification)

SPECIFICATIONS OF OPTION: Q (multiple selections)

COATING (For the detail, refer to our web site.)

/C01: Silicone coating

/C02: Polyurethane coating

/C03: Rubber coating

TERMINAL SCREW MATERIAL

/S01: Stainless steel

EX-FACTORY SETTING

/SET: Preset according to the Ordering Information Sheet
(No. ESU-1714)

GENERAL SPECIFICATIONS

Construction: Plug-in

Connection: M3.5 screw terminals

Screw terminal: Chromated steel (standard) or stainless steel

Housing material: Flame-resistant resin (black)

Isolation: Input to output to power

At burnout: Downscale ≤ -10 %, Upscale ≥ 110 %, Output ≤ 0 mA not available

Programming: Via front keys

- Input Type
- Moving average
- Burnout
- etc.

For detailed information, refer to the instruction manual.

■ DISPLAY

LED: 8 mm (.31") 7 segment, red

Number of display digits: 4 digits for DATA display; 2 digits for ITEM display

PV indication: Input signal in engineering unit

Overrange indication: LEDs blinking

Burnout indication: LEDs blinking and the PLC turns on.

Power saving mode: Displays turn off if the keys are untouched for a preset time period

LEDs: Red; the PL1 turns on with negative polarity and the PL2 turns on with burnout or programming error.

INPUT SPECIFICATIONS**Maximum leadwire resistance:** 200 Ω per wire (3-wire)**Sensing current:** ≤ 0.5 mA**Input min. step:** 0.1 ('1' for ≥ ±1000)**Default setting:** Pt 100 (JIS '97, IEC) 0 - 100°C**Temperature range**

RTD	USABLE RANGE	
	°C	°F
JPt 100 (JIS '89)	-230 to +560	-382 to +1040
Pt 100 (JIS '89)	-230 to +900	-382 to +1652
Pt 100 (JIS '97, IEC)	-230 to +900	-382 to +1652
Pt 50Ω (JIS '81)	-230 to +700	-382 to +1292
Ni 508.4Ω	-100 to +330	-148 to +626
Pt 1000	-230 to +900	-382 to +1652
Ni 100	-100 to +250	-148 to +482
Cu 10Ω @25°C	-210 to +310	-346 to +590

Note 1: Set the upper range temperature with a larger value than the lower range temperature value.

Note 2: Inverted output is available with the configuration.

Note 3: Operational range is of -15 to +115% or in the usable range as indicated above.

OUTPUT SPECIFICATIONS**DC Current:** 0.0 - 20.0 mA DC**Operational range:** 0.0 - 24.0 mA DC**Minimum increment:** 0.1 mA**Default setting:** 4.0 - 20.0 mA DC**DC Voltage****Code V1:** -1.00 - +1.00 V DC**Operational range:** -1.15 - +1.15 V DC**Minimum increment:** 10 mV**Code V2:** -10.0 - +10.0 V DC**Operational range:** -11.5 - +11.5 V DC**Minimum increment:** 100 mV

Note: Set to the 100 % output with a larger value than the 0 % output value.

Default setting:**Code V1:** -1.00 - +1.00 V DC**Code V2:** -10.0 - +10.0 V DC**INSTALLATION****Power consumption****•AC:**

Approx. 4 VA at 100 V

Approx. 5 VA at 200 V

Approx. 6 VA at 264 V

•DC: Approx. 3.5 W (100 mA at 24 V)**Operating temperature:** -5 to +55°C (23 to 131°F)**Operating humidity:** 30 to 90 %RH (non-condensing)**Mounting:** Surface or DIN rail**Weight:** 280 g (0.62 lb)**PERFORMANCE****Accuracy:** Input + output**Input:** ±0.3°C (±0.54°F) typical

±0.5°C (±0.9°F) for Cu 10

Output: ±0.05 %**Min. span required to ensure the accuracy:**

20% of the nominal I/O range

Display accuracy: Input accuracy ±1 digit**Temp. coefficient:** ±0.015 %/°C (±0.008 %/°F)**Response time:** ≤ 0.5 sec. (0 - 90 %)**Burnout response time:** ≤ 2 sec.**Line voltage effect:** ±0.1 % over voltage range**Insulation resistance:** ≥ 100 MΩ with 500 V DC**Dielectric strength:** 2000 V AC @1 minute (input to output to power to ground)**STANDARDS & APPROVALS****EU conformity:**

EMC Directive

EMI EN 61000-6-4

EMS EN 61000-6-2

Low Voltage Directive

EN 61010-1

Installation Category II


Pollution Degree 2

Input or output to power: Reinforced insulation (300 V)

Input to output: Basic insulation (300 V)


RoHS Directive

EXTERNAL VIEW




Refer to the instruction manual for detailed procedures.

EXTERNAL DIMENSIONS & TERMINAL ASSIGNMENTS unit: mm [inch]



• When mounting, no extra space is needed between units.

SCHEMATIC CIRCUITRY & CONNECTION DIAGRAM



Specifications are subject to change without notice.