

**Space-saving Dual Output Signal Conditioners
Mini-MW Series**


ISOLATOR

Functions & Features

- Galvanically isolating the input and output signals
- Universal power input
- High-density mounting

Typical Applications

- Isolation between control room and field instrumentation
- Eliminating ground loops



MODEL: W2YV-[1][2][3]-[4][5]

ORDERING INFORMATION

- Code number: W2YV-[1][2][3]-[4][5]
 - Specify a code from below for each of [1] through [5].
(e.g. W2YV-6A6-M/Q)
 - Specify the specification for option code /Q
(e.g. /C01 /V01)
- Note: When the user requires a current and a voltage output, specify the current to be the Output 1 which allows a greater load.

[1] INPUT

Current
A: 4 - 20 mA DC (Input resistance 250 Ω)
 Voltage
6: 1 - 5 V DC (Input resistance 1 MΩ min.)

[2] OUTPUT 1

Current
A: 4 - 20 mA DC (Load resistance 750 Ω max.)
 Voltage
6: 1 - 5 V DC (Load resistance 5000 Ω min.)

[3] OUTPUT 2

Y: None
 Current
A: 4 - 20 mA DC (Load resistance 350 Ω max.)
 Voltage
6: 1 - 5 V DC (Load resistance 5000 Ω min.)

[4] POWER INPUT

AC Power
M: 85 - 264 V AC (Operational voltage range 85 - 264 V, 47 - 66 Hz)
 DC Power
R2: 11 - 27 V DC
 (Operational voltage range 11 - 27 V, ripple 10 %p-p max.)

[5] OPTIONS

blank: none
 /Q: With options (specify the specification)

SPECIFICATIONS OF OPTION: Q (multiple selections)

- COATING (For the detail, refer to our web site.)
 /C01: Silicone coating
 /C02: Polyurethane coating
 /C03: Rubber coating
 ADJUSTMENT
 /V01: Multi-turn fine adjustment
 TERMINAL SCREW MATERIAL
 /S01: Stainless steel

GENERAL SPECIFICATIONS

- Construction:** Plug-in
Connection: M3 screw terminals (torque 0.8 N·m)
Screw terminal: Chromated steel (standard) or stainless steel
Housing material: Flame-resistant resin (black)
Isolation: Input to output 1 to output 2 to power
Overrange output: Approx. -10 to +120 % at 1 - 5 V
Zero adjustment: -5 to +5 % (front)
Span adjustment: 95 to 105 % (front)
 Adjustable individually for each output 1 and output 2.

INPUT SPECIFICATIONS

- DC Current:
 Shunt resistor attached to the input terminals (0.5 W)

INSTALLATION

Power Consumption

•AC:

Approx. 4 VA at 100 V

Approx. 5 VA at 200 V

Approx. 6 VA at 240 V

•DC: Approx. 3 W

Operating temperature: -5 to +55°C (23 to 131°F)

Operating humidity: 30 to 90 %RH (non-condensing)

Mounting: Surface or DIN rail

Weight: 200 g (0.44 lb)

PERFORMANCE in percentage of span

Accuracy: $\pm 0.1\%$

Temp. coefficient: $\pm 0.015\%/^{\circ}\text{C}$ ($\pm 0.008\%/^{\circ}\text{F}$)


Response time: ≤ 0.5 sec. (0 - 90 %)

Line voltage effect: $\pm 0.1\%$ over voltage range

Insulation resistance: $\geq 100\text{ M}\Omega$ with 500 V DC


Dielectric strength: 2000 V AC @1 minute (input to output
1 to output 2 to power to ground)

EXTERNAL DIMENSIONS unit: mm [inch]




• When mounting, no extra space is needed between units.

TERMINAL ASSIGNMENTS unit: mm [inch]



Input shunt resistor attached for current input.

SCHEMATIC CIRCUITRY & CONNECTION DIAGRAM



* Input shunt resistor attached for current input.
Note: The section enclosed by broken line is only with 2nd output option.



Specifications are subject to change without notice.