

ORDERING INFORMATION

Model : PSP20

PLEASE FILL IN THIS SECTION



Model
Company
Name
P/O No.

FACTORY USE ONLY



Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales Rep.	Approved by (Factory)
	Issued by (Factory)
	Ser No.

■ INSTRUCTION

Select an option or specify the value within the allowable range for the item to be changed from the standard setting. The standard setting will be applied if not specified.

ITEM	STANDARD SETTING	EX-FACTORY	FACTORY INTERNAL CHECK
■ Action Reverse Input 4 mA DC, output stem moves downward (Input 1 V DC, output stem moves downward) Direct Input 20 mA DC, output stem moves downward (Input 5 V DC, output stem moves downward)	Reverse	<input type="checkbox"/> Reverse <input type="checkbox"/> Direct	<input type="checkbox"/>
■ Stem operation at low input	Stop	<input type="checkbox"/> Stop <input type="checkbox"/> Move downward <input type="checkbox"/> Move upward	<input type="checkbox"/>
■ Output Same as input signal. Reversed input signal.	Same as input signal	<input type="checkbox"/> Same as input signal <input type="checkbox"/> Reversed input signal	<input type="checkbox"/>
■ Output stem operation distance	60 mm	<input type="checkbox"/> 60 mm <input type="checkbox"/> 40 mm	<input type="checkbox"/>