

ORDERING INFORMATION

MODEL : R7G4HML-6-SVF4

PLEASE FILL IN THIS SECTION



Model

Company

Name

P/O No.

FACTORY USE ONLY



Job No.

Ser No.

Sales

Approved by
(Sales office)

Issued by
(Sales office)

Approved by
(Factory)

Set by
(Factory)

Ser No.

Specify the items you want to change. Default setting will be used if not specified.

DEFAULT shows values in case of nothing specified.

■ INPUT RANGE SETTING

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 0	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ -1 to +1 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ 0 to 1 V DC		
	☐ -0.5 to +0.5 V DC		
	☐ -20 to +20 mA DC		
	☐ 4 to 20 mA DC		
	☐ 0 to 20 mA DC		
	☐ CH DISABLE		
INPUT 1	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ -1 to +1 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ 0 to 1 V DC		
	☐ -0.5 to +0.5 V DC		
	☐ -20 to +20 mA DC		
	☐ 4 to 20 mA DC		
	☐ 0 to 20 mA DC		
	☐ CH DISABLE		

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 2	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ -1 to +1 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ 0 to 1 V DC		
	☐ -0.5 to +0.5 V DC		
	☐ -20 to +20 mA DC		
	☐ 4 to 20 mA DC		
	☐ 0 to 20 mA DC		
	☐ CH DISABLE		
INPUT 3	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ -1 to +1 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ 0 to 1 V DC		
	☐ -0.5 to +0.5 V DC		
	☐ -20 to +20 mA DC		
	☐ 4 to 20 mA DC		
	☐ 0 to 20 mA DC		
	☐ CH DISABLE		

■ SCALING

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 0	-32000 to +32000	to	0 to 10000	☐
INPUT 1	-32000 to +32000	to	0 to 10000	☐
INPUT 2	-32000 to +32000	to	0 to 10000	☐
INPUT 3	-32000 to +32000	to	0 to 10000	☐

■ AVERAGING

ITEM	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
AVERAGING	1, 2, 4, 8, 16, 32, 64, 128, 256		1	☐