

ORDERING INFORMATION

MODEL : R7G4HML-6-SVF8N

PLEASE FILL IN THIS SECTION



Model
Company
Name
P/O No.

FACTORY USE ONLY



Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales	Approved by (Factory)
	Set by (Factory)
Ser No.	

Specify the items you want to change. Default setting will be used if not specified.

DEFAULT shows values in case of nothing specified.

■ INPUT RANGE SETTING

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 0	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ CH DISABLE		
INPUT 1	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ CH DISABLE		
INPUT 2	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ CH DISABLE		
INPUT 3	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ CH DISABLE		

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 4	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ CH DISABLE		
INPUT 5	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ CH DISABLE		
INPUT 6	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ CH DISABLE		
INPUT 7	☐ -10 to +10 V DC	-10 to +10 V DC	☐
	☐ -5 to +5 V DC		
	☐ 0 to 10 V DC		
	☐ 0 to 5 V DC		
	☐ 1 to 5 V DC		
	☐ CH DISABLE		

■ SCALING

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 0	-32000 to +32000* ¹	to	0 to 255	☐
INPUT 1	-32000 to +32000* ¹	to	0 to 255	☐
INPUT 2	-32000 to +32000* ¹	to	0 to 255	☐
INPUT 3	-32000 to +32000* ¹	to	0 to 255	☐
INPUT 4	-32000 to +32000* ¹	to	0 to 255	☐
INPUT 5	-32000 to +32000* ¹	to	0 to 255	☐
INPUT 6	-32000 to +32000* ¹	to	0 to 255	☐
INPUT 7	-32000 to +32000* ¹	to	0 to 255	☐

*1 If you use MECHATROLINK-I (17 byte) or MECHATROLINK-II (17 byte), set the scaling value in the range of 0-255.

■ AVERAGING

ITEM	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
AVERAGING	1, 2, 4, 8, 16, 32, 64, 128		1	☐

■ MECHATROLINK SETTING

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
MECHATROLINK SETTING	☐ MECHATROLINK-II (17 byte mode) ☐ MECHATROLINK-II (32 byte mode) ☐ MECHATROLINK-I (17 byte mode)	MECHATROLINK-II (17 byte mode)	☐