

# ORDERING INFORMATION

# MODEL : R7G4HH-A-SVF4

**PLEASE FILL IN THIS SECTION**



Model \_\_\_\_\_

Company \_\_\_\_\_

Name \_\_\_\_\_

P/O No. \_\_\_\_\_

**FACTORY USE ONLY**



Job No. \_\_\_\_\_

Ser No. \_\_\_\_\_

Sales \_\_\_\_\_

Approved by (Sales office) \_\_\_\_\_

Issued by (Sales office) \_\_\_\_\_

Approved by (Factory) \_\_\_\_\_

Set by (Factory) \_\_\_\_\_

Ser No. \_\_\_\_\_

**Specify the items you want to change. Default setting will be used if not specified.**

DEFAULT shows values in case of nothing specified.

**■ INPUT RANGE**

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 0	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH DISABLE	-10 to +10 V DC	<input type="checkbox"/>
INPUT 1	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH DISABLE	-10 to +10 V DC	<input type="checkbox"/>

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 2	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH DISABLE	-10 to +10 V DC	<input type="checkbox"/>
INPUT 3	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH DISABLE	-10 to +10 V DC	<input type="checkbox"/>

■ TRANSFER RATE

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
TRANSFER RATE	<input type="checkbox"/> 12 Mbps	12 Mbps	<input type="checkbox"/>
	<input type="checkbox"/> 6 Mbps		

■ STATION ADDRESS

ITEM	AVAILABLE RANGE	SET VALUE	DEFAULT VALUE	Factory Internal check
STATION ADDRESS	Full duplex: 01 to 39H Half duplex: 01 to 3CH		01H	<input type="checkbox"/>

■ SCALING

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 0	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 1	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 2	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 3	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>

■ AVERAGING

ITEM	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
AVERAGING	1, 2, 4, 8, 16, 32, 64, 128, 256		1	<input type="checkbox"/>