

ORDERING INFORMATION MODEL : R7D-DC16A, R7D-DC16B R7D-DC8C, R7D-DC8E

PLEASE FILL IN THIS SECTION



| |
|---------|
| Model |
| Company |
| Name |
| P/O No. |

FACTORY USE ONLY



| | |
|----------|-------------------------------|
| Job No. | Approved by (Sales office) |
| Ser. No. | Issued by (Sales office) |
| Sales | Approved by (Factory) |
| | Set by (Factory) |

Ser. No. _____

Specify the items you want to change. Default setting will be used if not specified.

■ BAUD RATE (B.RATE Switch)

| ITEM | SET VALUE | DEFAULT VALUE | Factory Internal check |
|-----------|--|---------------|--------------------------|
| BAUD RATE | <input type="checkbox"/> 125 kbps (0) | 125 kbps (0) | <input type="checkbox"/> |
| | <input type="checkbox"/> 250 kbps (1) | | |
| | <input type="checkbox"/> 500 kbps (2) | | |
| | <input type="checkbox"/> Auto tracking (3) | | |

■ NODE ADDRESS (NODE ADD. Switch)

| SETTING RANGE | SET VALUE | DEFAULT VALUE | Factory Internal check |
|---------------|-----------|---------------|--------------------------|
| 1 - 63 | | 0 | <input type="checkbox"/> |

■ EXTENSION (SW1-1, 2) *

| ITEM | SET VALUE | DEFAULT VALUE | Factory Internal check |
|-----------|---|----------------------------|--------------------------|
| EXTENSION | <input type="checkbox"/> No extension (OFF, OFF) | No extension (OFF, OFF) | <input type="checkbox"/> |
| | <input type="checkbox"/> Discrete input 8 or 16 points (ON, OFF) | | |
| | <input type="checkbox"/> Discrete output 8 or 16 points (OFF, ON) | | |

* Not usable with R7D-DC8C.

■ OUTPUT AT THE LOSE OF COMMUNICATION (SW1-4, applied for basic module)

| ITEM | SET VALUE | DEFAULT VALUE | Factory Internal check |
|-------------------------------------|---|-----------------|--------------------------|
| OUTPUT AT THE LOSE OF COMMUNICATION | <input type="checkbox"/> Hold the output (maintains the last data received normally) | Hold the output | <input type="checkbox"/> |
| | <input type="checkbox"/> Reset the output (turned off) | | |

■ INTERFACE SETTING

| PARAMETER | SETTING RANGE | SET VALUE | DEFAULT VALUE | Factory Internal check |
|-----------------------|-----------------------------|-----------|----------------|--------------------------|
| Communication Timeout | 0 - 32767 (1 = 0.1 sec.) | | 10 (1.0 sec.) | <input type="checkbox"/> |
| Status Data ** | OFF: Disable ON: Enable | | OFF: Disable | <input type="checkbox"/> |

* Not usable with R7D-DC8C.