

ORDERING INFORMATION

MODEL : R7D-YS2, R7D-YS2A

PLEASE FILL IN THIS SECTION



Model
Company
Name
P/O No.

FACTORY USE ONLY



Job No.	Approved by (Sales office)
Ser. No.	Issued by (Sales office)
Sales	Approved by (Factory)
	Set by (Factory)

Ser. No. _____

Specify the items you want to change. Default setting will be used if not specified.

■ BAUD RATE (B.RATE Switch)

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
BAUD RATE	<input type="checkbox"/> 125 kbps (0)	125 kbps (0)	<input type="checkbox"/>
	<input type="checkbox"/> 250 kbps (1)		
	<input type="checkbox"/> 500 kbps (2)		
	<input type="checkbox"/> Auto tracking (3)		

■ NODE ADDRESS (NODE ADD. Switch)

SETTING RANGE	SET VALUE	DEFAULT VALUE	Factory Internal check
1 - 63		0	<input type="checkbox"/>

■ EXTENSION (SW1-1, 2)

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
EXTENSION	<input type="checkbox"/> No extension (OFF, OFF)	No extension (OFF, OFF)	<input type="checkbox"/>
	<input type="checkbox"/> Discrete input 8 or 16 points (ON, OFF)		
	<input type="checkbox"/> Discrete output 8 or 16 points (OFF, ON)		

■ OUTPUT AT THE LOSE OF COMMUNICATION (SW1-4, applied for basic module)

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT AT THE LOSE OF COMMUNICATION	<input type="checkbox"/> Hold the output (*) (maintains the last data received normally)	Hold the output	<input type="checkbox"/>
	<input type="checkbox"/> Reset the output (to -15 %)		

■ SCALING

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT 0	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
OUTPUT 1	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>

■ INTERFACE SETTING

PARAMETER	SETTING RANGE	SET VALUE	DEFAULT VALUE	Factory Internal check
Communication Timeout	0 – 32767 (1 = 0.1 sec.)		10 (1.0 sec.)	<input type="checkbox"/>
Status Data	OFF: Disable ON: Enable		OFF: Disable	<input type="checkbox"/>