

ORDERING INFORMATION

MODEL : R7E-DC16A, R7E-DC16B

PLEASE FILL IN THIS SECTION



Model
Company
Name
P/O No.

FACTORY USE ONLY



Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales	Approved by (Factory)
	Set by (Factory)
	Ser No.

Specify the items you want to change. Default setting will be used if not specified.

DEFAULT shows values in case of nothing specified.

■ ETHERNET PARAMETERS

ITEM	AVAILABLE VALUE	SET VALUE				DEFAULT VALUE	Factory Internal check
IP Address	0 to 255 (integer)					192.168.0.1	<input type="checkbox"/>
Subnet Mask						255.255.255.0	<input type="checkbox"/>
Default Gateway						192.168.0.100	<input type="checkbox"/>
Linger	0 to 32767 (integer)					1800	<input type="checkbox"/>
TCP Socket closed after no communication (Set 1800 for 180.0 sec.) for the preset time.						1800	
						1800	
						1800	

■ OUTPUT AT THE LOSE OF COMMUNICATION (BASIC MODULE)

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT AT THE LOSE OF COMMUNICATION	<input type="checkbox"/> Hold the output (maintains the last data received normally)	Hold the output	<input type="checkbox"/>
	<input type="checkbox"/> Reset the output (turned off)		

■ EXTENSION

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
EXTENSION	<input type="checkbox"/> No extension	No extension	<input type="checkbox"/>
	<input type="checkbox"/> Discrete input, 8 points / 16 points		
	<input type="checkbox"/> Discrete output, 8 points / 16 points		

■ OUTPUT AT THE LOSS OF COMMUNICATION (EXTENSION MODULE)

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT AT THE LOSS OF COMMUNICATION	<input type="checkbox"/> Hold the output (maintains the last data received normally)	Hold the output	<input type="checkbox"/>
	<input type="checkbox"/> Reset the output (turned off)		