ORDERING INFORMATION MODEL : R7FN-YS2

PLEASE FILL IN THIS SECTION	FACTORY USE ONLY	
Model	Job No.	Approved by (Sales office)
Company	Ser No.	Issued by (Sales office)
Name	Sales	Approved by (Factory)
P/O No.		Set by (Factory)
		Ser No.

Specify the items you want to change. Default setting will be used if not specified. DEFAULT shows values in case of nothing specified.

OUTPUT AT THE LOSE OF COMMUNICATION

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT AT THE LOSE OF COMMUNICATION	 Hold the output (*) (maintains the last data received normally) Reset the output (to -15%) 	Hold the output	

■ TRANSFER RATE

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
TRANSFER RATE	□ 12Mbps		Γ
	□ 6Mbps	12Mbps	

STATION ADDRESS

AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
01H to 3FH (hexadecimal)		01H	

SCALING

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT 0	-32000 to +32000	to	0 to 10000	
OUTPUT 1	-32000 to +32000	to	0 to 10000	