# ORDERING INFORMATION MODEL: R7HL-YS2

PLEASE FILL IN THIS SECTION	FACTORY USE ONLY	
Model	Job No.	Approved by (Sales office)
Company	Ser No.	Issued by (Sales office)
Name	Sales	Approved by (Factory)
P/O No.		Set by (Factory)

Specify the items you want to change. Default setting will be used if not specified. DEFAULT shows values in case of nothing specified.

## ■ OUTPUT AT THE LOSE OF COMMUNICATION

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT AT THE LOSE OF COMMUNICATION	☐ Hold the output (*) (maintains the last data received normally) ☐ Reset the output (to -15%)	Hold the output	

#### ■ TRANSFER RATE

I INANSI EN NATE			
ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
TRANSFER RATE	☐ 12Mbps	12Mbps	
	☐ 6Mbps		

### **■ STATION ADDRESS**

AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
01H to 3FH (hexadecimal)		01H	

## **■** SCALING

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT 0	-32000 to +32000	to	0 to 10000	
OUTPUT 1	-32000 to +32000	to	0 to 10000	