

ORDERING INFORMATION

**Model: R7HL-DAC15E, R7HL-DAC16A,
R7HL-DAC16B, R7HL-DAC16C,
R7HL-DAC16ES**

PLEASE FILL IN THIS SECTION

Model
Company
Name
P/O No.

FACTORY USE ONLY

Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales Rep.	Approved by (Factory)
	Issued by (Factory)
	Ser No.

Specify the items you want to change. Default setting will be used if not specified.
DEFAULT shows values in case of nothing specified.

■ OUTPUT AT THE LOSS OF COMMUNICATION SETTING

PARAMETER	SET VALUE	DEFAULT VALUE	Factory Internal check
OUTPUT AT THE LOSS OF COMMUNICATION	☐ Hold the output (maintains the last data received normally)	Hold the output	☐
	☐ Reset the output (turned off)		

■ TRANSFER RATE SETTING

PARAMETER	SET VALUE	DEFAULT VALUE	Factory Internal check
TRANSFER RATE	☐ 12 Mbps	12 Mbps	☐
	☐ 6 Mbps		

■ STATION ADDRESS SETTING

PARAMETER	SETTING RANGE	SET VALUE	DEFAULT VALUE	Factory Internal check
STATION ADDRESS	01H to 3FH (hexadecimal)		01H	☐