

# ORDERING INFORMATION

# MODEL : R3-LC2

## PLEASE FILL IN THIS SECTION



Model
Company
Name
P/O No.

## FACTORY USE ONLY



Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales	Approved by (Factory)
	Set by (Factory)
Ser No.	

**Specify the items you want to change. Default setting will be used if not specified.**

DEFAULT shows values in case of nothing specified.

### ■ INPUT RANGE SETTING

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 1	<input type="checkbox"/> 0.0 to 1.0 mV/V	0.0 to 1.0 mV/V	<input type="checkbox"/>
	<input type="checkbox"/> 0.0 to 3.0 mV/V		
	<input type="checkbox"/> UNUSED		
INPUT 2	<input type="checkbox"/> 0.0 to 1.0 mV/V	0.0 to 1.0 mV/V	<input type="checkbox"/>
	<input type="checkbox"/> 0.0 to 3.0 mV/V		
	<input type="checkbox"/> UNUSED		

### ■ CONVERSION RATE

ITEM	SET VALUE	DEFAULT VALUE	Factory Internal check
CONVERSION RATE	<input type="checkbox"/> 160 ms <input type="checkbox"/> 80 ms <input type="checkbox"/> 40 ms <input type="checkbox"/> 20 ms	160 ms	<input type="checkbox"/>

### ■ DATA RANGE

In case of strain gauge input type, as it is essential to adjust zero and span at field, only the setting items related to scaling can be specified.

### SCALING VALUES

CHANNEL	0 % SCALING VALUE	100 % SCALING VALUE	AVAILABLE VALUE	DEFAULT VALUE (0 % to 100 %)	Factory Internal check
INPUT 1			-32 000 to +32 000	0 to 10 000	<input type="checkbox"/>
INPUT 2			-32 000 to +32 000	0 to 10 000	<input type="checkbox"/>