

# ORDERING INFORMATION

# MODEL : R30SV4

**PLEASE FILL IN THIS SECTION**



Model
Company
Name
P/O No.

**FACTORY USE ONLY**



Job No.	Approved by (Sales office)
Ser No.	Issued by (Sales office)
Sales	Approved by (Factory)
	Set by (Factory)
	Ser No.

**Specify the items you want to change. Default setting will be used if not specified.**  
 DEFAULT shows values in case of nothing specified.

**INPUT RANGE SETTING**

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 1	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH Disable	-10 to +10 V DC	<input type="checkbox"/>
INPUT 2	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH Disable	-10 to +10 V DC	<input type="checkbox"/>

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 3	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH Disable	-10 to +10 V DC	<input type="checkbox"/>
INPUT 4	<input type="checkbox"/> -10 to +10 V DC <input type="checkbox"/> -5 to +5 V DC <input type="checkbox"/> -1 to +1 V DC <input type="checkbox"/> 0 to 10 V DC <input type="checkbox"/> 0 to 5 V DC <input type="checkbox"/> 1 to 5 V DC <input type="checkbox"/> 0 to 1 V DC <input type="checkbox"/> -0.5 to +0.5 V DC <input type="checkbox"/> -20 to +20 mA DC <input type="checkbox"/> 4 to 20 mA DC <input type="checkbox"/> 0 to 20 mA DC <input type="checkbox"/> CH Disable	-10 to +10 V DC	<input type="checkbox"/>

Default value for CH Disable.

#### ■ DATA RANGE

Set zero and full scale to each channel (zero scale to full scale)

CHANNEL	AVAILABLE VALUE	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 1	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 2	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 3	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>
INPUT 4	-32000 to +32000	to	0 to 10000	<input type="checkbox"/>

#### ■ CONVERSION RATE

CHANNEL	SET VALUE	DEFAULT VALUE	Factory Internal check
INPUT 1 to 4 CONVERSION RATE / CONVERSION ACCURACY	<input type="checkbox"/> 80 ms / $\pm 0.1\%$ <input type="checkbox"/> 40 ms / $\pm 0.2\%$ <input type="checkbox"/> 20 ms / $\pm 0.4\%$ <input type="checkbox"/> 10 ms / $\pm 0.8\%$	80ms / $\pm 0.1\%$	<input type="checkbox"/>