

# ORDERING INFORMATION      MODEL: 48N series WITH DIGITAL INDICATOR (48NDR, 48NDT, 48NDV, 48NDVA, 48NDVD)

PLEASE FILL IN THIS SECTION ↓ ↓ ↓	FACTORY USE ONLY ↓ ↓ ↓ ↓ ↓	
Model	Job No.	Approved by (Sales office)
Company	Ser No.	Issued by (Sales office)
Name	Sales	Approved by (Factory)
P/O No.		Set by (Factory)
		Ser No.

**Specify the items you want to change. Default setting will be used if not specified.**  
 DEFAULT shows values in case of nothing specified.

### ■ ALARM SETTING

ITEM	AVAILABLE RANGE	SET VALUE	DEFAULT VALUE	Factory Internal check
LL Setpoint	4-point alarm type	-1999 to 9999 (Specify within the user specified range for digital indication.)	(10% of the user specified range for digital indication)	<input type="checkbox"/>
L Setpoint	2-point or 4-point alarm type	-1999 to 9999 (Specify within the user specified range for digital indication.)	(30% of the user specified range for digital indication)	
H Setpoint	2-point or 4-point alarm type	-1999 to 9999 (Specify within the user specified range for digital indication.)	(70% of the user specified range for digital indication)	
HH Setpoint	4-point alarm type	-1999 to 9999 (Specify within the user specified range for digital indication.)	(90% of the user specified range for digital indication)	

Note: Not necessary for None-alarm type. Setpoints must be LL < L < H < HH.

### ■ BAR COLOR SETTING (Points at which bar changes color)

ITEM	AVAILABLE RANGE	SET VALUE	DEFAULT VALUE	Factory Internal check
Color Setpoint 1	None-alarm type	-1999 to 9999 (Specify within the user specified range for digital indication.)	(30% of the user specified range for digital indication)	<input type="checkbox"/>
Color Setpoint 2	None-alarm type	-1999 to 9999 (Specify within the user specified range for digital indication.)	(70% of the user specified range for digital indication)	

Note: Not necessary for single color type (Bar LED Color code R, Y, G, B).  
 Setpoints must be Color Setpoint 1 < Color Setpoint 2.

■ ALARM ON TIME DELAY SETTING

ITEM	AVAILABLE RANGE		SET VALUE	DEFAULT VALUE	Factory Internal check
LL Setpoint ON Time Delay	4-point alarm type	0 to 15 (sec.)		0 (None)	<input type="checkbox"/>
L Setpoint ON Time Delay	2-point or 4-point alarm type	0 to 15 (sec.)		0 (None)	
H Setpoint ON Time Delay	2-point or 4-point alarm type	0 to 15 (sec.)		0 (None)	
HH Setpoint ON Time Delay	4-point alarm type	0 to 15 (sec.)		0 (None)	

■ MOVING AVERAGE SAMPLE NUMBERS SETTING

ITEM	AVAILABLE RANGE	SET VALUE	DEFAULT VALUE	Factory Internal check
Moving Average Sample Numbers	1, 2, 4, 8, 16 times		4	<input type="checkbox"/>