

ORDERING INFORMATION

MODEL: 48N series WITHOUT DIGITAL INDICATOR (48NAR, 48NAT, 48NAV, 48NAVA, 48NAVD)

PLEASE FILL IN THIS SECTION



Model

Company

Name

P/O No.

FACTORY USE ONLY



Job No.

Ser No.

Sales

Approved by
(Sales office)

Issued by
(Sales office)

Approved by
(Factory)

Set by
(Factory)

Ser No.

Specify the items you want to change. Default setting will be used if not specified.

DEFAULT shows values in case of nothing specified.

For 48N series, adjusting zero or span causes alarm setting cleared. In case of model 48NAM, potentiometer input type, as it is essential to adjust zero and span at field, the setting items related to alarm can not be specified.

■ ALARM SETTING

ITEM	AVAILABLE RANGE		SET VALUE	DEFAULT VALUE	Factory Internal check
LL Setpoint	4-point alarm type	0 to 100 (% of bar height)		10 (at 10%)	<input type="checkbox"/>
L Setpoint	2-point or 4-point alarm type	0 to 100 (% of bar height)		30 (at 30%)	
H Setpoint	2-point or 4-point alarm type	0 to 100 (% of bar height)		70 (at 70%)	
HH Setpoint	4-point alarm type	0 to 100 (% of bar height)		90 (at 90%)	

Note: Setpoints must be LL < L < H < HH.